



# SAFETY DATA SHEET

This SDS complies with REACH 1907/2006 and 2001/58/EC, GHS REVISION 5, OSHA 29CFR 1910.1200

## Section 1: Chemical Product and Company Identification

### MANUFACTURER'S NAME

IXL Technologies LLC  
2719 N. Parkland Blvd  
Pleasant View, Utah 84404

### EMERGENCY TELEPHONE

Chemtrec U.S.-Canada: 800-424-9300  
Chemtrec International: 703-527-3887  
Emergency: 801-458-1589  
Information: 801-732-8885  
Fax: 801-731-4499

Safety Data Sheet Competent Person:

Jordan Olsen Jordan.olsen@ixldirect.com

DATE PREPARED:

September 8, 2015

**REVISION DATE: September 8, 2015**

PRODUCT NAME:

**IXL Premium Grease #1 NLGI**

FORMULA:

Preparation/Mixture

PRODUCT USE:

Greasing and lubricating heavy machinery

## Section 2: Hazards Identification



### GHS Hazard Class

Acute Toxicity (Oral) – Category 3  
Skin Corrosion/Irritation – Category 2  
Carcinogenicity – Category 1B  
Aspiration toxicity – Category 1  
Danger

Signal word:

Hazard Statement:

H315: Causes skin irritation  
H335: May cause respiratory irritation  
H302: Harmful if swallowed  
H332: Harmful if inhaled  
H350: May cause cancer

Precautionary Statements:

Prevention

P201: Obtain special instructions before use  
P264: Wash hands thoroughly after handling  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray  
P270: Do not eat, drink or smoke when using this product

Response

P302 + P352: IF ON SKIN: Wash with plenty of water  
P332+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308 + P310 + P311: If exposed or concerned immediately call a POISON CENTER or doctor/physician if you feel unwell.  
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Storage

P330: Rinse mouth

Disposal

P405: Store locked up  
P501: Dispose of contents/container in accordance with waste disposal requirements of your country, state, or local authorities

Hazards not otherwise classified (HNOC) or not covered by GHS - Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning may clog the skin pores resulting disorders like acne/folliculitis. Used grease may contain harmful impurities/harmful extraneous substances.

HAZARD CLASSIFICATION:

Not classified as hazardous based on IATA, IMDG, and DOT.

FIRE AND EXPLOSION:

Not considered flammable or combustible, but this product will burn if involved in a fire. Product emits toxic fumes when burned.

POTENTIAL HEALTH EFFECTS:

<1 % of mixture consists of ingredients of unknown acute toxicity

APPEARANCE:

Deep green



NFPA Rating:

Component	Health (Blue)	Flammability (Red)	Reactivity (Yellow)	Special (White)
IXL Premium All Purpose Grease #1 NLGI	2	1	0	----

### Section 3: Composition, Information on Ingredients

PRODUCT COMPOSITION	APP- ROX %	CAS NO.	EC NO.	CANADA DSL
Mineral Oil (petroleum)	70 - 80	8042-47-5	232-455-8	Y
Calcium Thickener	5 - 25	26264-06-2	247-557-8	Y
Petroleum Distillates	1- 10	TS	Y	Y

Some items on this SDS may be designated as trade secrets (TS). Bonafide requests for disclosure of trade secret information to medical personnel must be made in accordance with the provisions contained in 29 CFR 1910.1200 I 1-13.

### Section 4: First Aid Measures

#### Description of First Aid Measures

Inhalation	Remove to fresh air. If not breathing, provide CPR (cardio pulmonary resuscitation). Get immediate medical attention.
Skin Contact	Immediately wash skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing.
Eye Contact	Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.
Ingestion	If swallowed do not induce vomiting, give large quantities of water to drink. Never give anything to an unconscious person. Get immediate medical attention.

#### Most important symptoms and effects, both acute and delayed

Symptoms/Injuries after Inhalation	May cause respiratory tract irritation.
Symptoms/Injuries after Skin Contact	May cause skin irritation.
Symptoms/Injuries after Eye Contact	May cause eye irritation.
Symptoms/Injuries after Ingestion	May be harmful if swallowed. Symptoms might include diarrhea.

#### Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately.

### Section 5: Fire-fighting Measures

#### Suitable extinguishing media

#### Special hazards arising from the substance or mixture

#### Protective actions fire-fighters

#### Further information

Use water spray, foam, dry powder, carbon dioxide, dry sand.  
 Hazardous combustion products may include a complex mixture of airborne solid and liquid particulates and gases (smoke), carbon monoxide, and unidentified inorganic and organic compounds  
 Wear standard protective equipment and self contained breathing apparatus for firefighting if necessary.  
 Use water spray to cool unopened containers.



## Section 6: Accidental Release Measures

### Personal precautions, protective equipment, and emergency procedures

Wear proper personal protective equipment.

### Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent spills or contaminated rinse water from entering sewers or watercourses.

### Methods and materials for containment and cleaning up

In case of small spills, absorb with inert materials such as earth or dry sand. Place in a chemical waste container.

In case of large spills, dike the spill, if possible. Call emergency services. Absorb the chemical.

**Reference to other Sections** For personal protection reference section 8. For disposal reference section 13.

## Section 7: Handling and Storage

### Precautions for safe handling

Wear proper protective equipment when handling this material.

Avoid contact with skin or eyes.

Wash hands after handling this material.

Appropriate container should be used for disposal.

For precautions see section 2.

### Conditions for safe storage, including any incompatibilities

Keep containers sealed until ready for use.

Avoid excessive long-term storage temperatures to prolong shelf life. Maximum storage temperature: 120°F.

Store in well ventilated areas.

Store upright in a cool, dry place.

Utilize chemical segregation.

Follow all applicable local regulations for handling and storage.

### Specific uses

This product is intended for greasing and lubricating heavy machinery

## Section 8: Exposure Controls/Personal Protection

### Control Parameters

PRODUCT COMPOSITION	ACGIH TLV	OSHA PEL	NIOSH REL
Mineral Oil (petroleum) Mist	5.0 mg/m <sup>3</sup>	--	--

### Exposure controls

VENTILATION:

Always provide good general, mechanical room ventilation where this chemical/material is used.

RESPIRATORY PROTECTION:

Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

PROTECTIVE GLOVES:

Neoprene, butyl, or nitrile rubber gloves are recommended.

EYE PROTECTION:

Recommend eye protection using safety glasses or goggles.

SKIN PROTECTION:

Suitable protective clothing to prevent skin contact

WORK/HYGIENE PRACTICES:

Avoid contact with eyes. Wash hands after handling.

OTHER EQUIPMENT:

Make safety shower, eyewash stations, and hand washing equipment available in the work area.



## Section 9: Physical and Chemical Properties

	PRODUCT CRITERIA
APPEARANCE - COLOR:	Deep Green
PHYSICAL STATE:	Semi-solid
ODOR:	Slightly hydrocarbon
ODOR THRESHOLD	Data not available
PH	N/A
FLASH POINT:	204 °C (400 °F)
LOWER EXPLOSIVE LIMIT; UPPER EXPLOSIVE LIMIT	Data not available
FLAMMABILITY (Solid, gas)	Data not available
EXPLOSIVE PROPERTIES	Not classified
OXIDIZING PROPERTIES	No data available
SPECIFIC GRAVITY (@25 °C):	@ 15 °C: 0.87, 7.506 (lbs/gal)
EVAPORATION RATE:	<1
% VOLATILE by VOLUME	No data available
PARTITION COEFFICIENT	No data available
AUTO IGNITION TEMPERATURE	No data available
DECOMPOSITION TEMPERATURE	No data available
BOILING POINT:	No data available
MELTING POINT:	No data available
VAPOR PRESSURE	@ Ambient temp. < 0.13 kPa (< 1 mm Hg)
VAPOR DENSITY (AIR = 1)	< 1
SOLUBILITY IN WATER:	Not Soluble
VISCOSITY	No data available

## Section 10: Stability and Reactivity

Reactivity:	Reacts with strong oxidizers.
Chemical Stability:	Stable under recommended conation.
Possibility of Hazardous Reactions:	Will not occur under normal temperatures and pressures.
Conditions to Avoid:	Heat, direct sunshine, sparks, and other sources of ignition.
Incompatibility (Materials to Avoid):	Strong oxidizing agents, heat, open flame.
Hazardous Decomposition Products:	None

## Section 11: Toxicological Information

GHS Required Criteria	Toxicity Criteria	Toxicity Information	Comments	Chemical Constituent
Acute Toxicity	LD50 (Oral/Rat):	1086-1980 mg/kg	Category 3	Calcium Thickener
Skin Corrosion/Irritation	Irritating to the skin (Human)			Calcium Thickener
Serious Eye Damage / Eye Irritation	Corrosive to ocular tissue			Calcium Thickener
Respiratory or Skin Sensitization		Data not available		
Germ Cell Mutagenicity		Data not available		
Carcinogenicity	NTP			
	IARC	Suspected of causing cancer (dependent on level of refinement)	Category 1B	Mixture of Distillates and Residual Oils (petroleum)
	OSHA			
Reproductive Toxicity		Data not available		
STOT -- Single Exposure		Data not available		
STOT -- Repeated Exposure		Data not available		
Aspiration Hazard	If this liquid is swallowed, aspiration into the lungs may result in chemical pneumonitis.			Mineral Oil (petroleum)
	May be fatal if swallowed and enters airways		Category 1	Mixture of Distillates and Residual Oils (petroleum)

STOT = Specific Target Organ Toxicity



## Section 12: Ecological Information

		Chemical Constituent
Toxicity:	LC50 Barnacle Larva (Balanus balanoides)(Crustacean) 3mg/l, 96hr.	Calcium Thickener
	Slightly harmful to the aquatic environment	Mineral Oil (petroleum)
Persistence and degradability:	No information is available.	
Bioaccumulative potential	No information is available.	
Mobility in soil:	No information is available.	
PBT and vPvB assessment:	PBT/vPvB assessment not available as chemical assessment not required/not conducted	
Other adverse effects:	No information is available.	

## Section 13: Disposal Considerations

**Waste from residues/unused products:** Follow the waste disposal requirements of your country, state, or local authorities.

**Contaminated packaging:** Contaminated packaging material should be disposed of as stated above for residues and unused product.

**Rinsate:** Do not dispose of rinse water containing product in a sanitary sewer system or stormwater drainage system.

## Section 14: Transport Information

**DOT TRANSPORT:** Not Regulated

**ADR = International Carriage of Dangerous Goods by Road** Not Regulated

**RAIL TRANSPORT:** Not Regulated

**SEA TRANSPORT:** IMDG Not Regulated

**AIR TRANSPORT:** IATA/ICAO Not Regulated

## Section 15: Regulatory Information

**TOXIC SUBSTANCE CONTROL ACT (TSCA) STATUS:**

This product is in compliance with rules, regulations, and orders of TSCA. All components are either listed on the TSCA inventory or are considered exempt.

**SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III SECTION 313 SUPPLIER NOTIFICATION:**

This regulation requires submission of annual reports of toxic chemical(s) that appear in section 313 of the Emergency Planning and Community Right To Know Act of 1986 and 40 CFR 372. This information must be included in all SDS's that are copied and distributed for the material.

The Section 313 toxic chemicals contained in this product are: None

**CALIFORNIA PROPOSITION 65:**

This regulation requires a warning for California Proposition 65 chemical(s) under the statute.

The California proposition 65 chemical(s) contained in this product are: None

**STATE RIGHT-TO-KNOW TOXIC SUBSTANCE OR HAZARDOUS SUBSTANCE LIST:**

Massachusetts's hazardous substance(s): Calcium Thickener

Pennsylvania hazardous substance code(s): Calcium Thickener

New Jersey Calcium Thickener

**CANADA:**

WHMIS-2015: This SDS is in compliance with WHMIS 2015 (HPR / new HPA)



## Section 16: Other Information

Initial issue date: September 8, 2015  
Final revision date: September 8, 2015  
Revision Number: 0  
Revision explanation: Initial version  
Information Sources: RTECS, ECHA, REACH, OSHA 29CFR 1910.1200.

“Disclaimer: This document is generated to distribute health, safety and environmental data. It is not a specification sheet and none of the displayed data should be construed as a specification. Information on this SDS sheet was obtained from sources which we believe are reliable, and we believe that the information is complete and accurate. However, the information is provided without any warranty, express or implied, regarding its correctness. Some of the information presented and conclusions drawn are from sources other than direct test data of the substance. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may also be beyond our knowledge. It is the user’s responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. If the product is used as a component in another product, this SDS information may not be applicable. For these reasons, we do not assume any responsibility and expressly disclaim liability for any loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.”

SDS AUTHORED BY:

**aēgis**  
ENVIRONMENTAL STRATEGIES  
[WWW.AEGIS-EHS.COM](http://WWW.AEGIS-EHS.COM)